

As part of our **FOAM and UPHOLSTERY** range, **F80** is a web spray adhesive designed for using the substrates listed here.



Foam



Fabric



Plywood



CA Compliant



No Hazardous Air  
Pollutant



Web Spray



CO-REZ  
Technology



Heat Resistant  
up to 200°F/ 94°C.

## PRODUCT DESCRIPTION

**Tensorgrip® F80** is a very aggressive, high build pressure sensitive adhesive designed to bond porous substrates while maintaining a high level of tack. Low VOC California Compliant SCAQMD 1168 Rule. Useful for bonding for Foam, Fabric, and Wood. Formulated with CO-REZ Technology, which is an exceptional formulation incorporating a highly engineered resin and gas matrix. The result: Great Coverage from Less Canister Weight.

## ADVANTAGES

- Repositionable
- California Compliant Low VOC SCAQMD Rule 1168
- Very Aggressive, High Tack Adhesive
- Single Sided Application
- High Build Web Spray
- HAPS Free
- High Strength, long-term bond
- 100% Adhesive Transfer to Substrate
- Fully Portable
- No ODS (ozone depleting substances)

## DIRECTIONS FOR USE

**Tensorgrip® F80** is designed as a portable, self-contained spray system for field or shop applications.

- Apply adhesive to one or both surfaces to be mated, at 80% to 100% coverage. Spraying both surfaces will result in a stronger, more permanent bond.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical. Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in 1-3 days.
- Canister system will spray adequately above 60° F.
- Canister system should be kept in a warm area. In the event that the canister gets abnormally chilled, freezes or give poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.

- Notice!!! Do not store at temperatures over 120° F.

### CANISTER STORAGE/CHANGE OVER

- If you choose to leave the hose and spray gun on the canister, leave the canister valve in the open position. Do not disconnect the hose/gun from the canister. Close and lock the spray gun. To change or disconnect canister: Turn canister valve to the off position, spray out remaining adhesive from the hose, disconnect the hose and spray gun from the canister
- Reconnect the hose and spray gun to a new canister of adhesive and turn the canister valve to re-pressurize. Or if you are NOT connecting to a new canister, connect hose to canister of cleaner (sold separately) and spray out until liquid is clear as the indication the hose/gun is clean.

### CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES	
Total Solids	30–38%
VOC Content	43.13 g/L (Canister) & 32.5% by weight (Aerosol)
Color	Clear or Red
System Flammability	Flammable
Solvent System	Methyl Acetate
Dry time	2–4 mins dependent on temp & humidity
Open time	Long (1+ hours)
Shelf Life	12 months from date of manufacture

PACKAGING	
650 mL	Aerosol Can
7L	Disposable Canister
22L	Disposable Canister
108L	Returnable Canister
216L	Returnable Canister

### APPLICATION TOOLS

TOOL	PART NUMBER	CANISTER SIZES			
		7 LITER	22 LITER	108 LITER	216 LITER
Hoses	M130-6 (6')	x			
	M130-12 (12')		x	x	x
	M130-18 (18')		x	x	x
	M130-25 (25')			x	x
	M130-36 (36')				x
	M130-50 (50')				x
Spray Guns	M120 (standard gun)	x	x	x	x
Spray Tip	M201 (2"-6"Low/Medium Build Adjustable Spray)	x	x	x	x
Hose Splitter	M300 (2-way splitter with 1 cap)			x	x

### HANDLING AND STORAGE

- Consult Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test product to determine suitability for your particular application prior to use in production

**DISCLAIMER OF WARRANTY:** Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.



## SAFETY DATA SHEET

### Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

#### 1. Identification

##### Product identifier

**Product name** Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol  
**Product number** USA

##### Recommended use of the chemical and restrictions on use

**Application** Aerosol Spray Adhesive

##### Details of the supplier of the safety data sheet

**Supplier** Quin Global US, Inc.  
 5510 F St  
 Omaha NE 68117  
 (402) 731 3636  
 (402) 731 1473  
 marketing.us@quin-global.com

##### Emergency telephone number

**Emergency telephone** Chemtrec: 1 800 424 9300

#### 2. Hazard(s) identification

##### Classification of the substance or mixture

**Physical hazards** Flam. Gas 2 - H221 Flam. Aerosol 2 - H223 Press. Gas, Liquefied - H280  
**Health hazards** Acute Tox. 4 - H302 Acute Tox. 4 - H332 Eye Irrit. 2A - H319 STOT SE 3 - H336  
**Environmental hazards** Aquatic Chronic 3 - H412

**Human health** The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

##### Label elements

##### Hazard symbols



##### Signal word

Warning

##### Hazard statements

H221 Flammable gas.  
 H223 Flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H302+H332 Harmful if swallowed or if inhaled.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

## Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

<b>Precautionary statements</b>	<p>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 If exposed or concerned: Get medical advice/ attention.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F.</p>
<b>Supplemental label information</b>	<p>AT(d) 7.5% of the mixture consists of ingredient(s) of unknown acute dermal toxicity.</p> <p>AT(o) 7.5% of the mixture consists of ingredient(s) of unknown acute oral toxicity.</p>
<b>Contains</b>	Methyl Acetate, Propane, Butane, Isopentane

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

<b>Methyl Acetate</b> CAS number: 79-20-9	<b>30-60%</b>
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Eye Irrit. 2A - H319 STOT SE 3 - H336	
<b>Propane</b> CAS number: 74-98-6	<b>10-25%</b>
<b>Classification</b> Press. Gas, Liquefied - H280 Acute Tox. 4 - H332 Simple Asphyxiant - USH03	
<b>Butane</b> CAS number: 106-97-8	<b>5-10%</b>
<b>Classification</b> Press. Gas, Liquefied - H280	

## Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

<b>Isopentane</b> CAS number: 78-78-4 M factor (Acute) = 1	<b>5-10%</b>
<b>Classification</b> Flam. Liq. 1 - H224 Eye Irrit. 2A - H319 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

The full text for all hazard statements is displayed in Section 16.

### 4. First-aid measures

#### Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
<b>Ingestion</b>	Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Skin Contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

#### Most important symptoms and effects, both acute and delayed

<b>General information</b>	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged or repeated exposure may cause the following adverse effects: Irritation of nose, throat and airway. Coughing. Headache.
<b>Ingestion</b>	Prolonged or repeated exposure may cause the following adverse effects: Gastrointestinal symptoms, including upset stomach. Nausea, vomiting. Diarrhea.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin.
<b>Eye contact</b>	Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

### 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

## Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### Special hazards arising from the substance or mixture

**Specific hazards** Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

### Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

### Environmental precautions

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

### Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 7. Handling and storage

### Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

### Specific end uses(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.

## 8. Exposure controls/Personal protection

### Control parameters

### Occupational exposure limits

**Methyl Acetate**

## Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm  
 Short-term exposure limit (15-minute): ACGIH 250 ppm  
 Long-term exposure limit (8-hour TWA): OSHA 200 ppm 610 mg/m<sup>3</sup>

### Propane

Long-term exposure limit (8-hour TWA): NIOSH: National Institute of Occupational Safety and Health 1800 mg/m<sup>3</sup> 1000 ppm  
 Long-term exposure limit (8-hour TWA): OSHA 1800 ppm 1000 mg/m<sup>3</sup>

### Butane

Long-term exposure limit (8-hour TWA): ACGIH 1000 ppm

### Isopentane

Long-term exposure limit (8-hour TWA): ACGIH 600 ppm  
 ACGIH = American Conference of Governmental Industrial Hygienists.  
 OSHA = Occupational Safety and Health Administration.

## Exposure controls

### Protective equipment



### Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

### Eye/face protection

Wear chemical splash goggles.

### Hand protection

Use protective gloves.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

### Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level exposures, a supplied air respirator should be used.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Aerosol.
Color	Clear.
Odor	Organic solvents.
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	0°C/32°F

## Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

<b>Flash point</b>	-104°C/-155°F Closed cup.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Upper flammable/explosive limit: 16 % Lower flammable/explosive limit: 1.4 %
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	.94
<b>Solubility(ies)</b>	Negligibly soluble in water
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Volatility</b>	Not available.
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 32.5% by weight .

### 10. Stability and reactivity

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended.
<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.
<b>Hazardous decomposition products</b>	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Aldehydes. Halogenated hydrocarbons.

### 11. Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

ATE oral (mg/kg) 1,172.61

##### Acute toxicity - dermal

ATE dermal (mg/kg) 2,579.74

##### Acute toxicity - inhalation

ATE inhalation (gases ppm) 26,470.59

ATE inhalation (vapours mg/l) 18.44

#### Toxicological information on ingredients.

##### Methyl Acetate

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 500.0



## Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 2,000.0 mg/kg)

Species Rat

ATE dermal (mg/kg) 1,100.0

### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 49.28

Species Rat

ATE inhalation (vapours mg/l) 11.0

### Propane

### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> gases ppmV) 1,442.0

Species Rat

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 1,442.0

Species Rat

ATE inhalation (gases ppm) 4,500.0

ATE inhalation (vapours mg/l) 11.0

### Butane

### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> gases ppmV) 658,000.0

Species Rat

**Inhalation** May be harmful if inhaled. May cause respiratory irritation.

**Ingestion** May be harmful if swallowed.

**Skin Contact** May be harmful in contact with skin. May cause skin irritation.

**Eye contact** May cause eye irritation.

### Isopentane

### Acute toxicity - oral

ATE oral (mg/kg) 100.0

### Acute toxicity - dermal

## Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

**ATE dermal (mg/kg)** 1,100.0

### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 1,280.0

**Species** Rat

**ATE inhalation (vapours mg/l)** 11.0

### Serious eye damage/irritation

**Serious eye damage/irritation** Irritation of eyes is assumed.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Ames Test Results: Negative.

### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause drowsiness or dizziness

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

### Aspiration hazard

**Aspiration hazard** Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

**General information** Absorbtion of large quantities may cause: Dizziness. Euphoria. Agitation. Convulsions. Narcosis.

## 12. Ecological information

### Bioaccumulative potential

**Partition coefficient** Not available.

## 13. Disposal considerations

### Waste treatment methods

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## 14. Transport information

**Air transport notes** Passenger Aircraft/Rail <75 kg. Cargo Aircraft Only <150 kg

### UN Number

**UN No. (International)** UN1950

**UN No. (TDG)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

**UN No. (DOT)** 1950

### UN proper shipping name

## Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

**Proper shipping name (TDG)** AEROSOLS, FLAMMABLE (PROPANE, BUTANE) 2.1, LTD QTY

**Proper shipping name (IMDG)** AEROSOLS, FLAMMABLE (PROPANE, BUTANE) 2.1, LTD QTY

**Proper shipping name (ICAO)** AEROSOLS, FLAMMABLE (PROPANE, BUTANE) 2.1, LTD QTY

**Proper shipping name (DOT)** AEROSOLS, FLAMMABLE (PROPANE, BUTANE) 2.1, LTD QTY

### Transport hazard class(es)

**DOT hazard class** 2.1

### Transport labels



### Packing group

**Packing group (International)** Not applicable.

## 15. Regulatory information

**National regulations** The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

**Guidance** CHIP for everyone HSG228.  
Workplace Exposure Limits EH40.  
Safety Data Sheets for Substances and Preparations.  
Approved Classification and Labelling Guide (Sixth edition) L131.

### US Federal Regulations

#### **CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

The following ingredients are listed or exempt:

#### **SARA 313 Emission Reporting**

The following ingredients are listed or exempt:

#### **SARA (311/312) Hazard Categories**

Hazard

### US State Regulations

#### **California Proposition 65 Carcinogens and Reproductive Toxins**

This product does not contain any chemicals known to the State of California to cause cancer, birth or any other reproductive harm.

#### **Massachusetts "Right To Know" List**

The following ingredients are listed or exempt:

#### **New Jersey "Right To Know" List**

The following ingredients are listed or exempt:

#### **Pennsylvania "Right To Know" List**

The following ingredients are listed or exempt:

### Inventories

#### **Canada - DSL/NDSL**

The following ingredients are listed or exempt:

## Tensorgrip F80 CA Compliant Pressure Sensitive Foam Adhesive Aerosol

### US - TSCA

Present.

### 16. Other information

<b>Revision date</b>	12/10/2020
<b>Revision</b>	24
<b>Supersedes date</b>	12/10/2020
<b>SDS No.</b>	24258
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H221 Flammable gas. H223 Flammable aerosol. H224 Extremely flammable liquid and vapor. H225 Highly flammable liquid and vapor. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. USH03 May displace oxygen and cause rapid suffocation
<b>ACA HMIS Health rating.</b>	Slight hazard. (1)
<b>ACA HMIS Flammability rating.</b>	Extremely flammable. (4)
<b>ACA HMIS Physical hazard rating.</b>	Normally stable. (0)
<b>ACA HMIS Personal protection rating.</b>	B

### DIRECTIONS FOR USE

### PRODUCT LOGO

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.